AMENDMENT UNDER 37 C.F.R. § 1.116 U.S. Appln. No. 09/695,140

- (Al) an olefin-unsaturated carboxylic acid-unsaturated carboxylate random copolymer, or both of an olefin-unsaturated carboxylic acid random copolymer and an olefin-unsaturated carboxylic acid-unsaturated carboxylate random copolymer, and
- (A2) a metal ion-neutralized olefin-unsaturated carboxylic acid-unsaturated carboxylate random copolymer, or both of a metal ion-neutralized olefin-unsaturated carboxylic acid random copolymer and a metal ion-neutralized olefin-unsaturated carboxylic acid-unsaturated carboxylate random copolymer;
- (B) 5 to 80 parts by weight of a fatty acid or fatty acid derivative having a molecular weight of at least 280; and
- (C) 0.1 to 10 parts by weight of a basic inorganic metal compound capable of neutralizing acidic groups in components A and B.
- 13. A solid golf ball comprising a solid core of at least one layer and a cover of at least one layer enclosing the solid core, wherein at least one layer of the solid core or the cover is made of a golf ball material comprising a heated mixture having a melt index of at least 1.0 dg/min which is composed of:
 - (A) 100 parts by weight of a base resin comprising one or a mixture of
 - (Al) an olefin-unsaturated carboxylic acid-unsaturated carboxylate random copolymer, or both of an olefin-unsaturated carboxylic acid random copolymer and an olefin-unsaturated carboxylic acid-unsaturated carboxylate random copolymer, and
 - (A2) a metal ion-neutralized olefin-unsaturated carboxylic acid-unsaturated carboxylate random copolymer, or both of a metal ion-neutralized olefin-unsaturated



AMENDMENT UNDER 37 C.F.R. § 1.116 U.S. Appln. No. 09/695,140

carboxylic acid random copolymer and a metal ion-neutralized olefin-unsaturated carboxylic acid-unsaturated carboxylate random copolymer;

- (B) 5 to 80 parts by weight of a fatty acid or fatty acid derivative having a molecular weight of at least 280; and
- (C) 0.1 to 10 parts by weight of a basic inorganic metal compound capable of neutralizing acidic groups in components A and B.
- 14. The solid golf ball of claim 13 comprising a one-layer cover enclosing the solid core, wherein the cover is made of the golf ball material.
- 15. The solid golf ball of claim 13 comprising a cover of at least two layers enclosing the solid core, wherein at least one inner cover layer other than the outermost cover layer is made of the golf ball material.
 - 16. A thread-wound golf ball comprising:

a thread-wound core composed of a solid center of at least one layer or a liquid center made of a liquid-filled center envelope, about which solid or liquid center has been wound a rubber thread, and

a cover of at least one layer which encloses the thread-wound core;

wherein the solid center or at least one layer of the cover is made of a golf ball material comprising a heated mixture having a melt index of at least 1.0 dg/min which is composed of:

(A) 100 parts by weight of a base resin comprising one or a mixture of

AMENDMENT UNDER 37 C.F.R. § 1.116 U.S. Appln. No. 09/695,140

- (Al) an olefin-unsaturated carboxylic acid-unsaturated carboxylate random copolymer, or both of an olefin-unsaturated carboxylic acid random copolymer and an olefin-unsaturated carboxylic/acid-unsaturated carboxylate random copolymer, and
- (A2) a metal ion-neutralized olefin-unsaturated carboxylic acid-unsaturated carboxylate random copolymer, or both of a metal ion-neutralized olefin-unsaturated carboxylic acid random copolymer and a metal ion-neutralized olefin-unsaturated carboxylic acid-unsaturated carboxylate random copolymer;
- (B) 5 to 80 parts by weight of a fatty acid or fatty acid derivative having a molecular weight of at least 280; and
- (C) 0.1 to 0 parts by weight of a basic inorganic metal compound capable of neutralizing acidic groups in components A and B.
- 17. The thread-wound golf ball of claim 16, wherein the thread-wound core is enclosed within a one-layer cover made of the golf ball material.
- 18. The thread-wound golf ball of claim 16, wherein the thread-wound core is enclosed within a cover having at least two layers, of which at least one inner layer other than the outermost layer is made of the golf ball material.